

Type	Order Number	Stock	Number of Teeth	Dimensions (mm)													
				D1	D4	D6	L1	L2	ap	A2	B2°	Clamp Screw	Clamp Bridge	Clamp Bridge Screw	Spring	Wrench	Insert
Long	AJX06R162SA16L	●	2	16	16	8.9	150	70	1	0.3	0°56'	TS25	—	—	—	①TKY08F	JOMO 06T215 ZZSR-∞
	172SA16L	●	2	17	16	9.9	150	20	1	0.3	—	TS25	—	—	—	①TKY08F	
	203SA20L	●	3	20	20	12.9	180	100	1	0.3	0°38'	TS25	—	—	—	①TKY08F	
	223SA20L	●	3	22	20	14.9	180	30	1	0.3	—	TS25	—	—	—	①TKY08F	
	AJX08R202SA20L	●	2	20	20	11.4	180	100	1.5	0.5	0°39'	TS33	—	—	—	②TKY08D	JOMO 080320 ZZSR-∞
	222SA20L	●	2	22	20	13.4	180	30	1.5	0.5	—	TS33	—	—	—	②TKY08D	
	253SA25L	●	3	25	25	16.4	200	120	1.5	0.5	0°32'	TS33	—	—	—	②TKY08D	
	283SA25L	●	3	28	25	19.4	200	40	1.5	0.5	—	TS33	—	—	—	②TKY08D	
	AJX09R252SA25L	●	2	25	25	14.9	200	120	2	1	0°32'	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	JDMO 09T320 ZDSR-∞
	282SA25L	●	2	28	25	17.9	200	40	2	1	—	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	
	303SA32L	●	3	30	32	20.0	200	120	2	1	1°02'	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	
	323SA32L	●	3	32	32	21.9	200	120	2	1	0°32'	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	
	353SA32L	●	3	35	32	24.9	200	50	2	1	—	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	
	404SA32L	●	4	40	32	29.9	250	50	2	1	—	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	
	404SA40L	□	4	40	40	29.9	250	70	2	1	0°56'	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	
	AJX12R302SA32L	●	2	30	32	18.3	200	120	2	1.5	1°02'	TS407	AMS4	AJS4012T15	ASS2	②TKY15D	JDMO 120420 ZDSR-∞
	322SA32L	●	2	32	32	20.3	200	120	2	1.5	0°33'	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	352SA32L	●	2	35	32	23.3	200	50	2	1.5	—	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	403SA32L	●	3	40	32	28.3	250	50	2	1.5	—	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	403SA40L	□	3	40	40	28.3	250	70	2	1.5	0°57'	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	403SA42L	★	3	40	42	28.3	250	70	2	1.5	1°48'	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	AJX14R503SA40L	□	3	50	40	38.2	250	50	2	2	—	TS54	AMS5	AJS5014T25	ASS3	②TKY25D	JDMO 140520 ZDSR-∞
	503SA42L	★	3	50	42	38.1	250	50	2	2	—	TS54	AMS5	AJS5014T25	ASS3	②TKY25D	
	634SA40L	□	4	63	40	51.1	250	50	2	2	—	TS54	AMS5	AJS5014T25	ASS3	②TKY25D	
	634SA42L	★	4	63	42	51.1	250	50	2	2	—	TS54	AMS5	AJS5014T25	ASS3	②TKY25D	
Extra Long	AJX06R162SA16EL	★	2	16	16	8.9	200	100	1	0.3	0°38'	TS25	—	—	—	①TKY08F	JOMO 06T215 ZZSR-∞
	172SA16EL	★	2	17	16	9.9	200	20	1	0.3	—	TS25	—	—	—	①TKY08F	
	AJX08R202SA20EL	★	2	20	20	11.4	250	130	1.5	0.5	0°30'	TS33	—	—	—	②TKY08D	JOMO 080320 ZZSR-∞
	222SA20EL	★	2	22	20	13.4	250	30	1.5	0.5	—	TS33	—	—	—	②TKY08D	
	AJX09R252SA25EL	★	2	25	25	14.9	300	180	2	1	0°22'	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	JDMO 09T320 ZDSR-∞
	282SA25EL	★	2	28	25	17.9	300	40	2	1	—	TS351	AMS3	AJS3010T10	ASS2	②TKY10D	
	AJX12R302SA32EL	★	2	30	32	18.3	300	180	2	1.5	0°42'	TS407	AMS4	AJS4012T15	ASS2	②TKY15D	JDMO 120420 ZDSR-∞
	322SA32EL	★	2	32	32	20.3	300	180	2	1.5	0°22'	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	352SA32EL	★	2	35	32	23.3	300	50	2	1.5	—	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	402SA32EL	★	2	40	32	28.3	350	50	2	1.5	—	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	402SA40EL	□	2	40	40	28.3	350	70	2	1.5	0°57'	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	
	402SA42EL	★	2	40	42	28.3	350	70	2	1.5	1°48'	TS43	AMS4	AJS4012T15	ASS2	②TKY15D	

★ Clamp Torque (N · m) : TS25=1.0, TS33=1.0, TS351=2.5, TS407=3.5, TS43=3.5, TS54=7.5, AJS3010T10=2.5, AJS4012T15=3.5, AJS5014T25=7.5