


INSERTS

Order Number	Grooving Width	Stock Grade			Dimensions (mm)				Geometry
		Coated	Cermet	Carbide	D1	S1	Re	L3	
		VP20MF	NX2525	UT120T					
	W3	L	L	L					
MGTL33125	1.25	★		●	9.525	4.76	0.2	1.2	MGTL...
33145	1.45	★		★	9.525	4.76	0.2	1.5	
33150	1.5	★	★	●	9.525	4.76	0.2	3	
33175	1.75	★	★	●	9.525	4.76	0.2	3	
33200	2	★	★	●	9.525	4.76	0.2	3	
33230	2.3	★		●	9.525	4.76	0.2	3	
33250	2.5	★	★	●	9.525	4.76	0.3	3	
33270	2.7	★		★	9.525	4.76	0.3	3	
33280	2.8	★		★	9.525	4.76	0.3	3	
33300	3	★	★	●	9.525	4.76	0.3	3	
33320	3.2	★			9.525	4.76	0.3	3	
33330	3.3	★		★	9.525	4.76	0.3	3	
33350	3.5	★		★	9.525	4.76	0.3	3	
33400	4	★	★	●	9.525	4.76	0.3	3	
MGTL43125	1.25	★	★	●	12.7	4.76	0.2	1.2	 
43145	1.45	★	★	★	12.7	4.76	0.2	1.5	
43150	1.5	★	●	●	12.7	4.76	0.2	3	
43175	1.75	★	★	●	12.7	4.76	0.2	3	
43200	2	★	●	●	12.7	4.76	0.2	3	
43230	2.3	★	★	●	12.7	4.76	0.2	3	
43250	2.5	★	★	●	12.7	4.76	0.3	4.5	
43260	2.6	★		●	12.7	4.76	0.3	4.5	
43270	2.7	★		★	12.7	4.76	0.3	4.5	
43280	2.8	★	★	●	12.7	4.76	0.3	4.5	
43300	3	★	★	●	12.7	4.76	0.3	4.5	
43320	3.2			●	12.7	4.76	0.3	4.5	
43330	3.3	★	★	●	12.7	4.76	0.3	4.5	
43350	3.5	★	★	●	12.7	4.76	0.3	4.5	
43400	4	★		●	12.7	4.76	0.3	4.5	
43420	4.2	★		●	12.7	4.76	0.4	4.5	
43430	4.3	★		●	12.7	4.76	0.4	4.5	
43450	4.5	★	★	●	12.7	4.76	0.4	4.5	
43470	4.7	★	★	★	12.7	4.76	0.4	4.5	
MGTL44500	5	★		★	12.7	6.35	0.4	4.5	
44600	6			●	12.7	6.35	0.4	4.5	

