

DRILLING (SOLID CARBIDE)

MMS

CARBIDE

DRILLING

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock DP7020	Order Number	Dimensions (mm)						Type
				L1	L2	L3	L6	L9	D4	
14.6	3	□	MMS1460S-DIN	114	66	64	—	48	16	2
	3	□	1460S-DIN-C	114	66	64	—	48	16	1
	5	□	1460L-DIN	132	84	82	—	48	16	2
	5	□	1460L-DIN-C	132	84	82	—	48	16	1
	3	★	1460X3DB	138	79	78	—	59	16	1
	5	★	1460X5DB	168	109	108	—	59	16	1
14.7	3	□	1470S-DIN	114	66	64	—	48	16	2
	3	□	1470S-DIN-C	114	66	64	—	48	16	1
	5	□	1470L-DIN	132	84	82	—	48	16	2
	5	□	1470L-DIN-C	132	84	82	—	48	16	1
	3	★	1470X3DB	138	79	78	—	59	16	1
	5	★	1470X5DB	168	109	108	—	59	16	1
14.8	3	□	1480S-DIN	114	66	64	—	48	16	2
	3	□	1480S-DIN-C	114	66	64	—	48	16	1
	5	□	1480L-DIN	132	84	82	—	48	16	2
	5	□	1480L-DIN-C	132	84	82	—	48	16	1
	3	★	1480X3DB	138	79	78	—	59	16	1
	5	★	1480X5DB	168	109	108	—	59	16	1
14.9	3	□	1490S-DIN	114	66	64	—	48	16	2
	3	□	1490S-DIN-C	114	66	64	—	48	16	1
	5	□	1490L-DIN	132	84	82	—	48	16	2
	5	□	1490L-DIN-C	132	84	82	—	48	16	1
	3	★	1490X3DB	138	79	78	—	59	16	1
	5	★	1490X5DB	168	109	108	—	59	16	1
15.0	3	●	1500S-DIN	114	66	64	—	48	16	2
	3	□	1500S-DIN-C	114	66	64	—	48	16	1
	5	●	1500L-DIN	132	84	82	—	48	16	2
	5	□	1500L-DIN-C	132	84	82	—	48	16	1
	3	★	1500X3DB	138	79	78	—	59	16	1
	5	★	1500X5DB	168	109	108	—	59	16	1
15.1	3	□	1510S-DIN	115	67	65	—	48	16	2
	3	□	1510S-DIN-C	115	67	65	—	48	16	1
	5	□	1510L-DIN	133	85	83	—	48	16	2
	5	□	1510L-DIN-C	133	85	83	—	48	16	1
	3	★	1510X3DB	142	83	81	—	59	16	1
	5	★	1510X5DB	174	115	112	—	59	16	1
15.2	3	□	1520S-DIN	115	67	65	—	48	16	2
	3	□	1520S-DIN-C	115	67	65	—	48	16	1
	5	□	1520L-DIN	133	85	83	—	48	16	2
	5	□	1520L-DIN-C	133	85	83	—	48	16	1
	3	★	1520X3DB	142	83	81	—	59	16	1
	5	★	1520X5DB	174	115	112	—	59	16	1
15.3	3	□	1530S-DIN	115	67	65	—	48	16	2
	3	□	1530S-DIN-C	115	67	65	—	48	16	1
	5	□	1530L-DIN	133	85	83	—	48	16	2
	5	□	1530L-DIN-C	133	85	83	—	48	16	1
	3	★	1530X3DB	142	83	81	—	59	16	1
	5	★	1530X5DB	174	115	112	—	59	16	1

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock DP7020	Order Number	Dimensions (mm)						Type
				L1	L2	L3	L6	L9	D4	
15.4	3	□	MMS1540S-DIN	115	67	65	—	48	16	2
	3	□	1540S-DIN-C	115	67	65	—	48	16	1
	5	□	1540L-DIN	133	85	83	—	48	16	2
	5	□	1540L-DIN-C	133	85	83	—	48	16	1
	3	★	1540X3DB	142	83	81	—	59	16	1
	5	★	1540X5DB	174	115	112	—	59	16	1
15.5	3	●	1550S-DIN	115	67	65	—	48	16	2
	3	□	1550S-DIN-C	115	67	65	—	48	16	1
	5	●	1550L-DIN	133	85	83	—	48	16	2
	5	□	1550L-DIN-C	133	85	83	—	48	16	1
	3	★	1550X3DB	142	83	81	—	59	16	1
	5	★	1550X5DB	174	115	112	—	59	16	1
15.6	3	□	1560S-DIN	115	67	65	—	48	16	2
	3	□	1560S-DIN-C	115	67	65	—	48	16	1
	5	□	1560L-DIN	133	85	83	—	48	16	2
	5	□	1560L-DIN-C	133	85	83	—	48	16	1
	3	★	1560X3DB	142	83	83	—	59	16	1
	5	★	1560X5DB	174	115	115	—	59	16	1
15.7	3	□	1570S-DIN	115	67	65	—	48	16	2
	3	□	1570S-DIN-C	115	67	65	—	48	16	1
	5	□	1570L-DIN	133	85	83	—	48	16	2
	5	□	1570L-DIN-C	133	85	83	—	48	16	1
	3	★	1570X3DB	142	83	83	—	59	16	1
	5	★	1570X5DB	174	115	115	—	59	16	1
15.8	3	□	1580S-DIN	115	67	65	—	48	16	2
	3	□	1580S-DIN-C	115	67	65	—	48	16	1
	5	□	1580L-DIN	133	85	83	—	48	16	2
	5	□	1580L-DIN-C	133	85	83	—	48	16	1
	3	★	1580X3DB	142	83	83	—	59	16	1
	5	★	1580X5DB	174	115	115	—	59	16	1
15.9	3	□	1590S-DIN	115	67	65	—	48	16	2
	3	□	1590S-DIN-C	115	67	65	—	48	16	1
	5	□	1590L-DIN	133	85	83	—	48	16	2
	5	□	1590L-DIN-C	133	85	83	—	48	16	1
	3	★	1590X3DB	142	83	83	—	59	16	1
	5	★	1590X5DB	174	115	115	—	59	16	1
16.0	3	●	1600S-DIN	115	67	65	—	48	16	2
	3	□	1600S-DIN-C	115	67	65	—	48	16	1
	5	●	1600L-DIN	133	85	83	—	48	16	2
	5	□	1600L-DIN-C	133	85	83	—	48	16	1
	3	★	1600X3DB	142	83	83	—	59	16	1
	5	★	1600X5DB	174	115	115	—	59	16	1
16.1	3	□	1610S-DIN	123	75	73	—	48	18	2
	3	□	1610S-DIN-C	123	75	73	—	48	18	1
	5	□	1610L-DIN	143	95	93	—	48	18	2
	5	□	1610L-DIN-C	143	95	93	—	48	18	1
	3	□	1610X3DB	148	89	86	—	59	18	1
	5	□	1610X5DB	182	123	119	—	59	18	1

● : Inventory maintained. ★ : Inventory maintained in Japan.

□ : Non stock, produced to order only.