

DRILLING (SOLID CARBIDE)

MNS

CARBIDE

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock TF15	Order Number	Dimensions (mm)					Type
				L1	L2	L3	L9	D4	
5.0	3	□	MNS0500S-DIN	66	30	28	36	6	2
	3	□	0500S-DIN-C	66	30	28	36	6	1
	5	□	0500L-DIN	82	46	44	36	6	2
	5	●	0500L-DIN-C	82	46	44	36	6	1
	8	□	0500-L8C	96	60	55	36	6	1
	10	□	0500-L10C	106	70	66	36	6	1
	12	●	0500-L12C	116	80	76	36	6	1
	15	□	0500-L15C	131	95	91	36	6	1
	20	●	0500-L20C	156	120	116	36	6	1
	25	□	0500-L25C	181	145	141	36	6	1
	30	●	0500-L30C	206	170	166	36	6	1
	5	★	0500LB	100	44	44	56	6	1
	10	★	0500X10DB	118	68	65	50	5	1
	20	★	0500X20DB	168	118	115	50	5	1
	30	★	0500X30DB	218	168	165	50	5	1
5.1	3	□	0510S-DIN	66	30	28	36	6	2
	3	□	0510S-DIN-C	66	30	28	36	6	1
	5	□	0510L-DIN	82	46	44	36	6	2
	5	●	0510L-DIN-C	82	46	44	36	6	1
	8	□	0510-L8C	102	66	62	36	6	1
	10	□	0510-L10C	113	77	73	36	6	1
	12	□	0510-L12C	124	88	84	36	6	1
	15	□	0510-L15C	140	104	100	36	6	1
	20	□	0510-L20C	168	132	128	36	6	1
	25	□	0510-L25C	195	159	155	36	6	1
	30	□	0510-L30C	223	187	183	36	6	1
	5	★	0510LB	100	44	44	56	6	1
	10	★	0510X10DB	127	75	72	52	6	1
	20	★	0510X20DB	182	130	127	52	6	1
	30	★	0510X30DB	237	185	182	52	6	1
5.2	3	□	0520S-DIN	66	30	28	36	6	2
	3	□	0520S-DIN-C	66	30	28	36	6	1
	5	□	0520L-DIN	82	46	44	36	6	2
	5	□	0520L-DIN-C	82	46	44	36	6	1
	8	□	0520-L8C	102	66	62	36	6	1
	10	□	0520-L10C	113	77	73	36	6	1
	12	□	0520-L12C	124	88	84	36	6	1
	15	□	0520-L15C	140	104	100	36	6	1
	20	□	0520-L20C	168	132	128	36	6	1
	25	□	0520-L25C	195	159	155	36	6	1
	30	□	0520-L30C	223	187	183	36	6	1
	5	★	0520LB	100	44	44	56	6	1
	10	□	0520X10DB	127	75	72	52	6	1
	20	□	0520X20DB	182	130	127	52	6	1
	30	□	0520X30DB	237	185	182	52	6	1

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock TF15	Order Number	Dimensions (mm)					Type
				L1	L2	L3	L9	D4	
5.3	3	□	MNS0530S-DIN	66	30	28	36	6	2
	3	□	0530S-DIN-C	66	30	28	36	6	1
	5	□	0530L-DIN	82	46	44	36	6	2
	5	□	0530L-DIN-C	82	46	44	36	6	1
	8	□	0530-L8C	102	66	62	36	6	1
	10	□	0530-L10C	113	77	73	36	6	1
	12	□	0530-L12C	124	88	84	36	6	1
	15	□	0530-L15C	140	104	100	36	6	1
	20	□	0530-L20C	168	132	128	36	6	1
	25	□	0530-L25C	195	159	155	36	6	1
	30	□	0530-L30C	223	187	183	36	6	1
	5	★	0530LB	100	44	44	56	6	1
	10	□	0530X10DB	127	75	72	52	6	1
	20	□	0530X20DB	182	130	127	52	6	1
	30	□	0530X30DB	237	185	182	52	6	1
5.4	3	□	0540S-DIN	66	30	28	36	6	2
	3	□	0540S-DIN-C	66	30	28	36	6	1
	5	□	0540L-DIN	82	46	44	36	6	2
	5	□	0540L-DIN-C	82	46	44	36	6	1
	8	□	0540-L8C	102	66	62	36	6	1
	10	□	0540-L10C	113	77	73	36	6	1
	12	□	0540-L12C	124	88	84	36	6	1
	15	□	0540-L15C	140	104	100	36	6	1
	20	□	0540-L20C	168	132	128	36	6	1
	25	□	0540-L25C	195	159	155	36	6	1
	30	□	0540-L30C	223	187	183	36	6	1
	5	★	0540LB	100	44	44	56	6	1
	10	□	0540X10DB	127	75	72	52	6	1
	20	□	0540X20DB	182	130	127	52	6	1
	30	□	0540X30DB	237	185	182	52	6	1
5.5	3	□	0550S-DIN	66	30	28	36	6	2
	3	□	0550S-DIN-C	66	30	28	36	6	1
	5	□	0550L-DIN	82	46	44	36	6	2
	5	●	0550L-DIN-C	82	46	44	36	6	1
	8	□	0550-L8C	102	66	62	36	6	1
	10	□	0550-L10C	113	77	73	36	6	1
	12	●	0550-L12C	124	88	84	36	6	1
	15	□	0550-L15C	140	104	100	36	6	1
	20	●	0550-L20C	168	132	128	36	6	1
	25	□	0550-L25C	195	159	155	36	6	1
	30	●	0550-L30C	223	187	183	36	6	1
	5	★	0550LB	100	44	44	56	6	1
	10	★	0550X10DB	127	75	72	52	6	1
	20	★	0550X20DB	182	130	127	52	6	1
	30	★	0550X30DB	237	185	182	52	6	1
5.55	3	□	0555S-DIN	66	30	28	36	6	2
	3	□	0555S-DIN-C	66	30	28	36	6	1
	5	□	0555L-DIN	82	46	44	36	6	2
	5	●	0555L-DIN-C	82	46	44	36	6	1

(Note) Please contact us for any geometry that is not in this catalogue (e.g. different diameter and length).

● : Inventory maintained. ★ : Inventory maintained in Japan.

□ : Non stock, produced to order only.