

DRILLING (SOLID CARBIDE)

MNS

CARBIDE

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock TF15	Order Number	Dimensions (mm)					Type
				L1	L2	L3	L9	D4	
6.2	3	□	MNS0620S-DIN	79	43	34	36	8	2
	3	□	0620S-DIN-C	79	43	34	36	8	1
	5	□	0620L-DIN	91	55	53	36	8	2
	5	□	0620L-DIN-C	91	55	53	36	8	1
	8	□	0620-L8C	113	77	73	36	8	1
	10	□	0620-L10C	126	90	86	36	8	1
	12	□	0620-L12C	139	103	99	36	8	1
	15	□	0620-L15C	158	122	118	36	8	1
	20	□	0620-L20C	191	155	151	36	8	1
	25	□	0620-L25C	223	187	183	36	8	1
	30	□	0620-L30C	256	220	216	36	8	1
	5	★	0620LB	109	52	52	57	7	1
	10	□	0620X10DB	141	88	85	53	7	1
	20	□	0620X20DB	206	153	150	53	7	1
	30	□	0620X30DB	271	218	215	53	7	1
6.3	3	□	0630S-DIN	79	43	34	36	8	2
	3	□	0630S-DIN-C	79	43	34	36	8	1
	5	□	0630L-DIN	91	55	53	36	8	2
	5	□	0630L-DIN-C	91	55	53	36	8	1
	8	□	0630-L8C	113	77	73	36	8	1
	10	□	0630-L10C	126	90	86	36	8	1
	12	□	0630-L12C	139	103	99	36	8	1
	15	□	0630-L15C	158	122	118	36	8	1
	20	□	0630-L20C	191	155	151	36	8	1
	25	□	0630-L25C	223	187	183	36	8	1
	30	□	0630-L30C	256	220	216	36	8	1
	5	★	0630LB	109	52	52	57	7	1
	10	□	0630X10DB	141	88	85	53	7	1
	20	□	0630X20DB	206	153	150	53	7	1
	30	□	0630X30DB	271	218	215	53	7	1
6.4	3	□	0640S-DIN	79	43	34	36	8	2
	3	□	0640S-DIN-C	79	43	34	36	8	1
	5	□	0640L-DIN	91	55	53	36	8	2
	5	□	0640L-DIN-C	91	55	53	36	8	1
	8	□	0640-L8C	113	77	73	36	8	1
	10	□	0640-L10C	126	90	86	36	8	1
	12	□	0640-L12C	139	103	99	36	8	1
	15	□	0640-L15C	158	122	118	36	8	1
	20	□	0640-L20C	191	155	151	36	8	1
	25	□	0640-L25C	223	187	183	36	8	1
	30	□	0640-L30C	256	220	216	36	8	1
	5	★	0640LB	109	52	52	57	7	1
	10	□	0640X10DB	141	88	85	53	7	1
	20	□	0640X20DB	206	153	150	53	7	1
	30	□	0640X30DB	271	218	215	53	7	1

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock TF15	Order Number	Dimensions (mm)					Type
				L1	L2	L3	L9	D4	
6.5	3	□	MNS0650S-DIN	79	43	34	36	8	2
	3	□	0650S-DIN-C	79	43	34	36	8	1
	5	□	0650L-DIN	91	55	53	36	8	2
	5	●	0650L-DIN-C	91	55	53	36	8	1
	8	□	0650-L8C	113	77	73	36	8	1
	10	□	0650-L10C	126	90	86	36	8	1
	12	●	0650-L12C	139	103	99	36	8	1
	15	□	0650-L15C	158	122	118	36	8	1
	20	●	0650-L20C	191	155	151	36	8	1
	25	□	0650-L25C	223	187	183	36	8	1
	30	●	0650-L30C	256	220	216	36	8	1
	5	★	0650LB	109	52	52	57	7	1
	10	★	0650X10DB	141	88	85	53	7	1
	20	★	0650X20DB	206	153	150	53	7	1
	30	★	0650X30DB	271	218	215	53	7	1
6.6	3	□	0660S-DIN	79	43	34	36	8	2
	3	□	0660S-DIN-C	79	43	34	36	8	1
	5	□	0660L-DIN	91	55	53	36	8	2
	5	□	0660L-DIN-C	91	55	53	36	8	1
	8	□	0660-L8C	118	82	78	36	8	1
	10	□	0660-L10C	132	96	92	36	8	1
	12	□	0660-L12C	146	110	106	36	8	1
	15	□	0660-L15C	167	131	127	36	8	1
	20	□	0660-L20C	202	166	162	36	8	1
	25	□	0660-L25C	237	201	197	36	8	1
	30	□	0660-L30C	272	236	232	36	8	1
	5	★	0660LB	109	56	56	53	7	1
	10	□	0660X10DB	147	94	91	53	7	1
	20	□	0660X20DB	217	164	161	53	7	1
	30	□	0660X30DB	287	234	231	53	7	1
6.7	3	□	0670S-DIN	79	43	34	36	8	2
	3	□	0670S-DIN-C	79	43	34	36	8	1
	5	□	0670L-DIN	91	55	53	36	8	2
	5	□	0670L-DIN-C	91	55	53	36	8	1
	8	□	0670-L8C	118	82	78	36	8	1
	10	□	0670-L10C	132	96	92	36	8	1
	12	□	0670-L12C	146	110	106	36	8	1
	15	□	0670-L15C	167	131	127	36	8	1
	20	□	0670-L20C	202	166	162	36	8	1
	25	□	0670-L25C	237	201	197	36	8	1
	30	□	0670-L30C	272	236	232	36	8	1
	5	★	0670LB	109	56	56	53	7	1
	10	★	0670X10DB	147	94	91	53	7	1
	20	★	0670X20DB	217	164	161	53	7	1
	30	★	0670X30DB	287	234	231	53	7	1

(Note) Please contact us for any geometry that is not in this catalogue (e.g. different diameter and length).

● : Inventory maintained. ★ : Inventory maintained in Japan.

□ : Non stock, produced to order only.

L078