

DRILLING (SOLID CARBIDE)

MNS

CARBIDE

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock TF15	Order Number	Dimensions (mm)					Type
				L1	L2	L3	L9	D4	
8.6	3	□	MNS0860S-DIN	88	48	46	40	10	2
	3	□	0860S-DIN-C	88	48	46	40	10	1
	5	□	0860L-DIN	102	62	60	40	10	2
	5	□	0860L-DIN-C	102	62	60	40	10	1
	8	□	0860-L8C	144	104	100	40	10	1
	10	□	0860-L10C	162	122	118	40	10	1
	12	□	0860-L12C	180	140	136	40	10	1
	15	□	0860-L15C	207	167	163	40	10	1
	20	□	0860-L20C	252	212	208	40	10	1
	25	□	0860-L25C	297	257	253	40	10	1
	30	□	0860-L30C	342	302	298	40	10	1
	5	★	0860LB	127	72	72	55	9	1
	10	□	0860X10DB	175	120	117	55	9	1
	20	□	0860X20DB	265	210	207	55	9	1
	30	□	0860X30DB	355	300	297	55	9	1
8.7	3	□	0870S-DIN	88	48	46	40	10	2
	3	□	0870S-DIN-C	88	48	46	40	10	1
	5	□	0870L-DIN	102	62	60	40	10	2
	5	□	0870L-DIN-C	102	62	60	40	10	1
	8	□	0870-L8C	144	104	100	40	10	1
	10	□	0870-L10C	162	122	118	40	10	1
	12	□	0870-L12C	180	140	136	40	10	1
	15	□	0870-L15C	207	167	163	40	10	1
	20	□	0870-L20C	252	212	208	40	10	1
	25	□	0870-L25C	297	257	253	40	10	1
	30	□	0870-L30C	342	302	298	40	10	1
	5	★	0870LB	127	72	72	55	9	1
	10	□	0870X10DB	175	120	117	55	9	1
	20	□	0870X20DB	265	210	207	55	9	1
	30	□	0870X30DB	355	300	297	55	9	1
8.8	3	□	0880S-DIN	88	48	46	40	10	2
	3	□	0880S-DIN-C	88	48	46	40	10	1
	5	□	0880L-DIN	102	62	60	40	10	2
	5	□	0880L-DIN-C	102	62	60	40	10	1
	8	□	0880-L8C	144	104	100	40	10	1
	10	□	0880-L10C	162	122	118	40	10	1
	12	□	0880-L12C	180	140	136	40	10	1
	15	□	0880-L15C	207	167	163	40	10	1
	20	□	0880-L20C	252	212	208	40	10	1
	25	□	0880-L25C	297	257	253	40	10	1
	30	□	0880-L30C	342	302	298	40	10	1
	5	★	0880LB	127	72	72	55	9	1
	10	□	0880X10DB	175	120	117	55	9	1
	20	□	0880X20DB	265	210	207	55	9	1
	30	□	0880X30DB	355	300	297	55	9	1

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock TF15	Order Number	Dimensions (mm)					Type
				L1	L2	L3	L9	D4	
8.9	3	□	MNS0890S-DIN	88	48	46	40	10	2
	3	□	0890S-DIN-C	88	48	46	40	10	1
	5	□	0890L-DIN	102	62	60	40	10	2
	5	□	0890L-DIN-C	102	62	60	40	10	1
	8	□	0890-L8C	144	104	100	40	10	1
	10	□	0890-L10C	162	122	118	40	10	1
	12	□	0890-L12C	180	140	136	40	10	1
	15	□	0890-L15C	207	167	163	40	10	1
	20	□	0890-L20C	252	212	208	40	10	1
	25	□	0890-L25C	297	257	253	40	10	1
	30	□	0890-L30C	342	302	298	40	10	1
	5	★	0890LB	127	72	72	55	9	1
	10	□	0890X10DB	175	120	117	55	9	1
	20	□	0890X20DB	265	210	207	55	9	1
	30	□	0890X30DB	355	300	297	55	9	1
9.0	3	□	0900S-DIN	88	48	46	40	10	2
	3	□	0900S-DIN-C	88	48	46	40	10	1
	5	□	0900L-DIN	102	62	60	40	10	2
	5	●	0900L-DIN-C	102	62	60	40	10	1
	8	□	0900-L8C	144	104	100	40	10	1
	10	□	0900-L10C	162	122	118	40	10	1
	12	●	0900-L12C	180	140	136	40	10	1
	15	□	0900-L15C	207	167	163	40	10	1
	20	●	0900-L20C	252	212	208	40	10	1
	25	□	0900-L25C	297	257	253	40	10	1
	30	●	0900-L30C	342	302	298	40	10	1
	5	★	0900LB	127	72	72	55	9	1
	10	★	0900X10DB	175	120	117	55	9	1
	20	★	0900X20DB	265	210	207	55	9	1
	30	★	0900X30DB	355	300	297	55	9	1
9.1	3	□	0910S-DIN	89	49	47	40	10	2
	3	□	0910S-DIN-C	89	49	47	40	10	1
	5	□	0910L-DIN	103	63	62	40	10	2
	5	□	0910L-DIN-C	103	63	62	40	10	1
	8	□	0910-L8C	151	111	107	40	10	1
	10	□	0910-L10C	170	130	126	40	10	1
	12	□	0910-L12C	189	149	145	40	10	1
	15	□	0910-L15C	217	177	173	40	10	1
	20	□	0910-L20C	265	225	221	40	10	1
	25	□	0910-L25C	312	272	268	40	10	1
	30	□	0910-L30C	360	320	316	40	10	1
	5	★	0910LB	136	80	76	56	10	1
	10	□	0910X10DB	182	127	124	55	10	1
	20	□	0910X20DB	277	222	219	55	10	1
	30	□	0910X30DB	372	317	314	55	10	1

(Note) Please contact us for any geometry that is not in this catalogue (e.g. different diameter and length).

● : Inventory maintained. ★ : Inventory maintained in Japan.

□ : Non stock, produced to order only.