

DRILLING (SOLID CARBIDE)

MNS

CARBIDE

DRILLING

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock TF15	Order Number	Dimensions (mm)					Type
				L1	L2	L3	L9	D4	
12.6	3	□	MNS1260S-DIN	107	62	60	45	14	2
	3	□	1260S-DIN-C	107	62	60	45	14	1
	5	□	1260L-DIN	124	79	77	45	14	2
	5	□	1260L-DIN-C	124	79	77	45	14	1
	8	□	1260-L8C	194	149	145	45	14	1
	10	□	1260-L10C	220	175	171	45	14	1
	12	□	1260-L12C	246	201	197	45	14	1
	15	□	1260-L15C	285	240	236	45	14	1
	20	□	1260-L20C	350	305	301	45	14	1
	5	★	1260LB	167	104	104	63	13	1
	10	□	1260X10DB	235	172	169	63	13	1
	20	□	1260X20DB	365	302	299	63	13	1
12.7	3	□	1270S-DIN	107	62	60	45	14	2
	3	□	1270S-DIN-C	107	62	60	45	14	1
	5	□	1270L-DIN	124	79	77	45	14	2
	5	□	1270L-DIN-C	124	79	77	45	14	1
	8	□	1270-L8C	194	149	145	45	14	1
	10	□	1270-L10C	220	175	171	45	14	1
	12	□	1270-L12C	246	201	197	45	14	1
	15	□	1270-L15C	285	240	236	45	14	1
	20	□	1270-L20C	350	305	301	45	14	1
	5	★	1270LB	167	104	104	63	13	1
	10	□	1270X10DB	235	172	169	63	13	1
	20	□	1270X20DB	365	302	299	63	13	1
12.8	3	□	1280S-DIN	107	62	60	45	14	2
	3	□	1280S-DIN-C	107	62	60	45	14	1
	5	□	1280L-DIN	124	79	77	45	14	2
	5	□	1280L-DIN-C	124	79	77	45	14	1
	8	□	1280-L8C	194	149	145	45	14	1
	10	□	1280-L10C	220	175	171	45	14	1
	12	□	1280-L12C	246	201	197	45	14	1
	15	□	1280-L15C	285	240	236	45	14	1
	20	□	1280-L20C	350	305	301	45	14	1
	5	★	1280LB	167	104	104	63	13	1
	10	□	1280X10DB	235	172	169	63	13	1
	20	□	1280X20DB	365	302	299	63	13	1
12.9	3	□	1290S-DIN	107	62	60	45	14	2
	3	□	1290S-DIN-C	107	62	60	45	14	1
	5	□	1290L-DIN	124	79	77	45	14	2
	5	□	1290L-DIN-C	124	79	77	45	14	1
	8	□	1290-L8C	194	149	145	45	14	1
	10	□	1290-L10C	220	175	171	45	14	1
	12	□	1290-L12C	246	201	197	45	14	1
	15	□	1290-L15C	285	240	236	45	14	1
	20	□	1290-L20C	350	305	301	45	14	1
	5	★	1290LB	167	104	104	63	13	1
	10	□	1290X10DB	235	172	169	63	13	1
	20	□	1290X20DB	365	302	299	63	13	1

Drill Dia. D1 (mm)	Hole Depth (l/d)	Stock TF15	Order Number	Dimensions (mm)					Type
				L1	L2	L3	L9	D4	
13.0	3	□	MNS1300S-DIN	107	62	60	45	14	2
	3	□	1300S-DIN-C	107	62	60	45	14	1
	5	□	1300L-DIN	124	79	77	45	14	2
	5	●	1300L-DIN-C	124	79	77	45	14	1
	8	□	1300-L8C	194	149	145	45	14	1
	10	□	1300-L10C	220	175	171	45	14	1
	12	●	1300-L12C	246	201	197	45	14	1
	15	□	1300-L15C	285	240	236	45	14	1
	20	●	1300-L20C	350	305	301	45	14	1
	5	★	1300LB	167	104	104	63	13	1
	10	★	1300X10DB	235	172	169	63	13	1
	20	★	1300X20DB	365	302	299	63	13	1
13.1	3	□	1310S-DIN	107	62	60	45	14	2
	3	□	1310S-DIN-C	107	62	60	45	14	1
	5	□	1310L-DIN	124	79	77	45	14	2
	5	□	1310L-DIN-C	124	79	77	45	14	1
	8	□	1310-L8C	200	155	151	45	14	1
	10	□	1310-L10C	227	182	178	45	14	1
	12	□	1310-L12C	254	209	205	45	14	1
	15	□	1310-L15C	294	249	245	45	14	1
	20	□	1310-L20C	362	317	313	45	14	1
	5	★	1310LB	176	112	108	64	14	1
	10	□	1310X10DB	243	179	176	64	14	1
	20	□	1310X20DB	378	314	311	64	14	1
13.2	3	□	1320S-DIN	107	62	60	45	14	2
	3	□	1320S-DIN-C	107	62	60	45	14	1
	5	□	1320L-DIN	124	79	77	45	14	2
	5	□	1320L-DIN-C	124	79	77	45	14	1
	8	□	1320-L8C	200	155	151	45	14	1
	10	□	1320-L10C	227	182	178	45	14	1
	12	□	1320-L12C	254	209	205	45	14	1
	15	□	1320-L15C	294	249	245	45	14	1
	20	□	1320-L20C	362	317	313	45	14	1
	5	★	1320LB	176	112	108	64	14	1
	10	□	1320X10DB	243	179	176	64	14	1
	20	□	1320X20DB	378	314	311	64	14	1
13.3	3	□	1330S-DIN	107	62	60	45	14	2
	3	□	1330S-DIN-C	107	62	60	45	14	1
	5	□	1330L-DIN	124	79	77	45	14	2
	5	□	1330L-DIN-C	124	79	77	45	14	1
	8	□	1330-L8C	200	155	151	45	14	1
	10	□	1330-L10C	227	182	178	45	14	1
	12	□	1330-L12C	254	209	205	45	14	1
	15	□	1330-L15C	294	249	245	45	14	1
	20	□	1330-L20C	362	317	313	45	14	1
	5	★	1330LB	176	112	108	64	14	1
	10	□	1330X10DB	243	179	176	64	14	1
	20	□	1330X20DB	378	314	311	64	14	1

(Note) Please contact us for any geometry that is not in this catalogue (e.g. different diameter and length).

● : Inventory maintained. ★ : Inventory maintained in Japan.

□ : Non stock, produced to order only.

L088