

DRILLING (SOLID CARBIDE)

CARBIDE

MAE,MAS

Drill Dia. D1 (mm)	Hole Depth (l/d)	Coolant (Int./Ext.)	Stock HT10	Order Number	Dimensions (mm)		
					L3	L1	D4
14.7	3	Ext.	□	MAE1470MB	72	130	15
	3	Int.	□	MAS1470MB	72	130	15
	6	Int.	□	MAS1470LB	115	173	15
14.8	3	Ext.	□	MAE1480MB	72	130	15
	3	Int.	□	MAS1480MB	72	130	15
	6	Int.	□	MAS1480LB	115	173	15
14.9	3	Ext.	□	MAE1490MB	72	130	15
	3	Int.	□	MAS1490MB	72	130	15
	6	Int.	□	MAS1490LB	115	173	15
14.96	3	Ext.	★	★ MAE1496MB	72	130	15
	3	Int.	★	★ MAS1496MB	72	130	15
	6	Int.	★	★ MAS1496LB	115	173	15
15.0	3	Ext.	★	MAE1500MB	72	130	15
	3	Int.	★	MAS1500MB	72	130	15
	6	Int.	●	MAS1500LB	115	173	15
15.1	3	Ext.	□	MAE1510MB	76	134	16
	3	Int.	□	MAS1510MB	76	134	16
	6	Int.	□	MAS1510LB	120	178	16
15.2	3	Ext.	□	MAE1520MB	76	134	16
	3	Int.	□	MAS1520MB	76	134	16
	6	Int.	□	MAS1520LB	120	178	16
15.3	3	Ext.	□	MAE1530MB	76	134	16
	3	Int.	□	MAS1530MB	76	134	16
	6	Int.	□	MAS1530LB	120	178	16
15.4	3	Ext.	□	MAE1540MB	76	134	16
	3	Int.	□	MAS1540MB	76	134	16
	6	Int.	□	MAS1540LB	120	178	16
15.5	3	Ext.	□	MAE1550MB	76	134	16
	3	Int.	□	MAS1550MB	76	134	16
	6	Int.	□	MAS1550LB	120	178	16
15.6	3	Ext.	□	MAE1560MB	76	134	16
	3	Int.	□	MAS1560MB	76	134	16
	6	Int.	□	MAS1560LB	120	178	16
15.7	3	Ext.	□	MAE1570MB	76	134	16
	3	Int.	□	MAS1570MB	76	134	16
	6	Int.	□	MAS1570LB	120	178	16
15.8	3	Ext.	□	MAE1580MB	76	134	16
	3	Int.	□	MAS1580MB	76	134	16
	6	Int.	□	MAS1580LB	120	178	16
15.9	3	Ext.	□	MAE1590MB	76	134	16
	3	Int.	□	MAS1590MB	76	134	16
	6	Int.	□	MAS1590LB	120	178	16
16.0	3	Ext.	★	MAE1600MB	76	134	16
	3	Int.	★	MAS1600MB	76	134	16
	6	Int.	●	MAS1600LB	120	178	16

★ : Standard hole size for rolled thread taps.

● : Inventory maintained. ★ : Inventory maintained in Japan.

□ : Non stock, produced to order only.

L100