

DRILLING (SOLID CARBIDE)

MHS

CARBIDE

DRILLING

Drill Dia. D1 (mm)	Hole Depth (l/d)	Coolant (Int./Ext.)	Stock VP15TF	Order Number	Dimensions (mm)				Type
					L3	L2	L1	D4	
10.2	1	Int.	□	MHS1020L040B	38.5	40	100	12	3
	6	Int.	□	1020L090B	88.5	90	150	12	4
	9	Int.	□	1020L120B	118.5	120	180	12	4
	12	Int.	□	1020L150B	148.5	150	210	12	4
	17	Int.	□	1020L200B	198.5	200	260	12	4
	22	Int.	□	1020L250B	248.5	250	310	12	4
	27	Int.	□	1020L300B	298.5	300	360	12	4
10.3	1	Int.	□	1030L040B	38.5	40	100	12	3
	6	Int.	□	1030L090B	88.5	90	150	12	4
	9	Int.	□	1030L120B	118.5	120	180	12	4
	12	Int.	□	1030L150B	148.5	150	210	12	4
	17	Int.	□	1030L200B	198.5	200	260	12	4
	22	Int.	□	1030L250B	248.5	250	310	12	4
	26	Int.	□	1030L300B	298.5	300	360	12	4
10.4	1	Int.	□	1040L040B	38.5	40	100	12	3
	6	Int.	□	1040L090B	88.5	90	150	12	4
	9	Int.	□	1040L120B	118.5	120	180	12	4
	12	Int.	□	1040L150B	148.5	150	210	12	4
	17	Int.	□	1040L200B	198.5	200	260	12	4
	21	Int.	□	1040L250B	248.5	250	310	12	4
	26	Int.	□	1040L300B	298.5	300	360	12	4
10.5	1	Int.	●	1050L040B	38.5	40	100	12	3
	6	Int.	●	1050L090B	88.5	90	150	12	4
	9	Int.	●	1050L120B	118.5	120	180	12	4
	12	Int.	●	1050L150B	148.5	150	210	12	4
	16	Int.	●	1050L200B	198.5	200	260	12	4
	21	Int.	●	1050L250B	248.5	250	310	12	4
	26	Int.	●	1050L300B	298.5	300	360	12	4
10.6	1	Int.	□	1060L040B	39	40	100	12	3
	6	Int.	□	1060L090B	89	90	150	12	4
	9	Int.	□	1060L120B	119	120	180	12	4
	12	Int.	□	1060L150B	149	150	210	12	4
	16	Int.	□	1060L200B	199	200	260	12	4
	21	Int.	□	1060L250B	249	250	310	12	4
	26	Int.	□	1060L300B	299	300	360	12	4
10.7	1	Int.	□	1070L040B	39	40	100	12	3
	6	Int.	□	1070L090B	89	90	150	12	4
	9	Int.	□	1070L120B	119	120	180	12	4
	11	Int.	□	1070L150B	149	150	210	12	4
	16	Int.	□	1070L200B	199	200	260	12	4
	21	Int.	□	1070L250B	249	250	310	12	4
	25	Int.	□	1070L300B	299	300	360	12	4
10.8	1	Int.	★	1080L040B	39	40	100	12	3
	6	Int.	★	1080L090B	89	90	150	12	4
	9	Int.	★	1080L120B	119	120	180	12	4
	11	Int.	★	1080L150B	149	150	210	12	4
	16	Int.	★	1080L200B	199	200	260	12	4
	21	Int.	★	1080L250B	249	250	310	12	4
	25	Int.	★	1080L300B	299	300	360	12	4

Drill Dia. D1 (mm)	Hole Depth (l/d)	Coolant (Int./Ext.)	Stock VP15TF	Order Number	Dimensions (mm)				Type
					L3	L2	L1	D4	
10.9	1	Int.	□	MHS1090L040B	39	40	100	12	3
	6	Int.	□	1090L090B	89	90	150	12	4
	8	Int.	□	1090L120B	119	120	180	12	4
	11	Int.	□	1090L150B	149	150	210	12	4
	16	Int.	□	1090L200B	199	200	260	12	4
	20	Int.	□	1090L250B	249	250	310	12	4
	25	Int.	□	1090L300B	299	300	360	12	4
11.0	1	Int.	●	1100L040B	39	40	100	12	3
	6	Int.	●	1100L090B	89	90	150	12	4
	8	Int.	●	1100L120B	119	120	180	12	4
	11	Int.	●	1100L150B	149	150	210	12	4
	16	Int.	●	1100L200B	199	200	260	12	4
	20	Int.	●	1100L250B	249	250	310	12	4
	25	Int.	●	1100L300B	299	300	360	12	4
11.1	1	Int.	□	1110L040B	39.5	40	100	12	3
	6	Int.	□	1110L090B	89.5	90	150	12	4
	8	Int.	□	1110L120B	119.5	120	180	12	4
	11	Int.	□	1110L150B	149.5	150	210	12	4
	15	Int.	□	1110L200B	199.5	200	260	12	4
	20	Int.	□	1110L250B	249.5	250	310	12	4
	24	Int.	□	1110L300B	299.5	300	360	12	4
11.2	1	Int.	□	1120L040B	39.5	40	100	12	3
	5	Int.	□	1120L090B	89.5	90	150	12	4
	8	Int.	□	1120L120B	119.5	120	180	12	4
	11	Int.	□	1120L150B	149.5	150	210	12	4
	15	Int.	□	1120L200B	199.5	200	260	12	4
	20	Int.	□	1120L250B	249.5	250	310	12	4
	24	Int.	□	1120L300B	299.5	300	360	12	4
11.3	1	Int.	□	1130L040B	39.5	40	100	12	3
	5	Int.	□	1130L090B	89.5	90	150	12	4
	8	Int.	□	1130L120B	119.5	120	180	12	4
	11	Int.	□	1130L150B	149.5	150	210	12	4
	15	Int.	□	1130L200B	199.5	200	260	12	4
	20	Int.	□	1130L250B	249.5	250	310	12	4
	24	Int.	□	1130L300B	299.5	300	360	12	4
11.4	1	Int.	□	1140L040B	39.5	40	100	12	3
	5	Int.	□	1140L090B	89.5	90	150	12	4
	8	Int.	□	1140L120B	119.5	120	180	12	4
	11	Int.	□	1140L150B	149.5	150	210	12	4
	15	Int.	□	1140L200B	199.5	200	260	12	4
	19	Int.	□	1140L250B	249.5	250	310	12	4
	24	Int.	□	1140L300B	299.5	300	360	12	4
11.5	1	Int.	●	1150L040B	39.5	40	100	12	3
	5	Int.	●	1150L090B	89.5	90	150	12	4
	8	Int.	●	1150L120B	119.5	120	180	12	4
	10	Int.	●	1150L150B	149.5	150	210	12	4
	15	Int.	●	1150L200B	199.5	200	260	12	4
	19	Int.	●	1150L250B	249.5	250	310	12	4
	24	Int.	●	1150L300B	299.5	300	360	12	4

(Note) Please contact us for any geometry that is not in this catalogue (e.g. different diameter and length).

● : Inventory maintained. ★ : Inventory maintained in Japan.

□ : Non stock, produced to order only.