

DRILLING (INDEXABLE TYPE)

TAW

CARBIDE

Order Number	Stock		Dimensions (mm)			Applicable Holder
	VP15TF	VP10H	D1	L2	S1	
TAWNH2650T	●	□	26.5	11.3	9.0	TAWSN 2700S32
2660T	□	□	26.6	11.3	9.0	
2670T	□	□	26.7	11.3	9.0	
2680T	□	□	26.8	11.3	9.0	
2690T	□	□	26.9	11.3	9.0	
2700T	●	□	27.0	11.2	9.0	
2710T	□	□	27.1	11.2	9.0	
2720T	□	□	27.2	11.2	9.0	
2730T	□	□	27.3	11.2	9.0	
2740T	□	□	27.4	11.2	9.0	
2750T	●	□	27.5	12.3	10.0	TAWSN 2800S32
2760T	□	□	27.6	12.3	10.0	
2770T	□	□	27.7	12.3	10.0	
2780T	□	□	27.8	12.3	10.0	
2790T	□	□	27.9	12.3	10.0	
2800T	●	□	28.0	12.2	10.0	
2810T	□	□	28.1	12.2	10.0	
2820T	□	□	28.2	12.2	10.0	
2830T	□	□	28.3	12.2	10.0	
2840T	□	□	28.4	12.2	10.0	
2850T	●	□	28.5	12.1	10.0	TAWSN 2900S32
2860T	□	□	28.6	12.1	10.0	
2870T	□	□	28.7	12.1	10.0	
2880T	□	□	28.8	12.1	10.0	
2890T	□	□	28.9	12.1	10.0	
2900T	●	□	29.0	12.0	10.0	
2910T	□	□	29.1	12.0	10.0	
2920T	□	□	29.2	12.0	10.0	
2930T	□	□	29.3	12.0	10.0	
2940T	□	□	29.4	12.0	10.0	
2950T	●	□	29.5	11.9	10.0	TAWSN 3000S32
2960T	□	□	29.6	11.9	10.0	
2970T	□	□	29.7	11.9	10.0	
2980T	□	□	29.8	11.9	10.0	
2990T	□	□	29.9	11.9	10.0	
3000T	●	□	30.0	11.8	10.0	
3010T	□	□	30.1	11.8	10.0	
3020T	□	□	30.2	11.8	10.0	
3030T	□	□	30.3	11.8	10.0	
3040T	□	□	30.4	11.8	10.0	

● : Inventory maintained. (Note: 1 insert in one case)

□ : Non stock, produced to order only.