

DRILLING (INDEXABLE TYPE)

TAW

CARBIDE

Order Number	Stock	Dimensions (mm)			Applicable Holder
	DP5010	D1	L2	S1	
TAWKH2650TG	●	26.5	10.4	9.0	TAWSN 2700S32
2660TG	□	26.6	10.4	9.0	
2670TG	□	26.7	10.4	9.0	
2680TG	□	26.8	10.4	9.0	
2690TG	□	26.9	10.4	9.0	
2700TG	●	27.0	10.3	9.0	
2710TG	□	27.1	10.3	9.0	
2720TG	□	27.2	10.3	9.0	
2730TG	□	27.3	10.3	9.0	
2740TG	□	27.4	10.3	9.0	
2750TG	●	27.5	11.3	10.0	TAWSN 2800S32
2760TG	□	27.6	11.3	10.0	
2770TG	□	27.7	11.3	10.0	
2780TG	□	27.8	11.3	10.0	
2790TG	□	27.9	11.3	10.0	
2800TG	●	28.0	11.2	10.0	
2810TG	□	28.1	11.2	10.0	
2820TG	□	28.2	11.2	10.0	
2830TG	□	28.3	11.2	10.0	
2840TG	□	28.4	11.2	10.0	
2850TG	●	28.5	11.1	10.0	TAWSN 2900S32
2860TG	□	28.6	11.1	10.0	
2870TG	□	28.7	11.1	10.0	
2880TG	□	28.8	11.1	10.0	
2890TG	□	28.9	11.1	10.0	
2900TG	●	29.0	11.0	10.0	
2910TG	□	29.1	11.0	10.0	
2920TG	□	29.2	11.0	10.0	
2930TG	□	29.3	11.0	10.0	
2940TG	□	29.4	11.0	10.0	
2950TG	●	29.5	10.9	10.0	TAWSN 3000S32
2960TG	□	29.6	10.9	10.0	
2970TG	□	29.7	10.9	10.0	
2980TG	□	29.8	10.9	10.0	
2990TG	□	29.9	10.9	10.0	
3000TG	●	30.0	10.8	10.0	
3010TG	□	30.1	10.8	10.0	
3020TG	□	30.2	10.8	10.0	
3030TG	□	30.3	10.8	10.0	
3040TG	□	30.4	10.8	10.0	

DRILLING

● : Inventory maintained. (Note: 1 insert in one case)

□ : Non stock, produced to order only.