


Dia. D1 (mm)	Hole Depth (l/d)	Order Number	Stock	Teeth	Dimensions (mm)					Maximum radial adjustment (mm)	Insert		
					L3	L2	L1	D4	D7				
28.5	2	MVX2850X2F32	●	2	64	84	139	32	42	0.8	SOMX094506-UM	TPS4	TIP15W
	3	2850X3F32	●	2	92.5	112.5	167.5	32	42	0.8	094506-UM	TPS4	TIP15W
29.0	2	2900X2F32	●	2	65	85	140	32	42	0.75	094506-UM	TPS4	TIP15W
	3	2900X3F32	●	2	94	114	169	32	42	0.75	094506-UM	TPS4	TIP15W
	4	2900X4F32	●	2	123	143	198	32	42	0.75	094506-UM	TPS4	TIP15W
	5	2900X5F32	●	2	152	172	227	32	42	0.75	094506-UM	TPS4	TIP15W
	6	2900X6F32	●	2	181	201	256	32	42	0.75	094506-UM	TPS4	TIP15W
29.5	2	2950X2F32	●	2	66	86	141	32	42	0.7	094506-UM	TPS4	TIP15W
	3	2950X3F32	●	2	95.5	115.5	170.5	32	42	0.7	094506-UM	TPS4	TIP15W
30.0	2	3000X2F32	●	2	67	87	142	32	42	0.65	094506-UM	TPS4	TIP15W
	3	3000X3F32	●	2	97	117	172	32	42	0.65	094506-UM	TPS4	TIP15W
	4	3000X4F32	●	2	127	147	202	32	42	0.65	094506-UM	TPS4	TIP15W
	5	3000X5F32	●	2	157	177	232	32	42	0.65	094506-UM	TPS4	TIP15W
	6	3000X6F32	●	2	187	207	262	32	42	0.65	094506-UM	TPS4	TIP15W
30.5	3	3050X3F32	●	2	98.5	118.5	173.5	32	42	0.6	094506-UM	TPS4	TIP15W
31.0	2	3100X2F32	●	2	69	89	144	32	42	0.55	094506-UM	TPS4	TIP15W
	3	3100X3F32	●	2	100	120	175	32	42	0.55	094506-UM	TPS4	TIP15W
	4	3100X4F32	●	2	131	151	206	32	42	0.55	094506-UM	TPS4	TIP15W
	2	3100X2F40	●	2	69	89	154	40	50	0.55	094506-UM	TPS4	TIP15W
	3	3100X3F40	●	2	100	120	185	40	50	0.55	094506-UM	TPS4	TIP15W
	4	3100X4F40	●	2	131	151	216	40	50	0.55	094506-UM	TPS4	TIP15W
	5	3100X5F40	●	2	162	182	247	40	50	0.55	094506-UM	TPS4	TIP15W
	6	3100X6F40	●	2	193	213	278	40	50	0.55	094506-UM	TPS4	TIP15W
31.5	3	3150X3F40	●	2	101.5	121.5	186.5	40	50	0.55	094506-UM	TPS4	TIP15W
32.0	2	3200X2F32	●	2	71	91	146	32	42	0.45	094506-UM	TPS4	TIP15W
	3	3200X3F32	●	2	103	123	178	32	42	0.45	094506-UM	TPS4	TIP15W
	4	3200X4F32	●	2	135	155	210	32	42	0.45	094506-UM	TPS4	TIP15W
	2	3200X2F40	●	2	71	91	156	40	50	0.45	094506-UM	TPS4	TIP15W
	3	3200X3F40	●	2	103	123	188	40	50	0.45	094506-UM	TPS4	TIP15W
	4	3200X4F40	●	2	135	155	220	40	50	0.45	094506-UM	TPS4	TIP15W
	5	3200X5F40	●	2	167	187	252	40	50	0.45	094506-UM	TPS4	TIP15W
	6	3200X6F40	●	2	199	219	284	40	50	0.45	094506-UM	TPS4	TIP15W
32.5	3	3250X3F40	●	2	104.5	124.5	189.5	40	50	0.45	094506-UM	TPS4	TIP15W
33.0	2	3300X2F32	●	2	73	93	148	32	42	0.4	094506-UM	TPS4	TIP15W
	3	3300X3F32	●	2	106	126	181	32	42	0.4	094506-UM	TPS4	TIP15W
	4	3300X4F32	●	2	139	159	214	32	42	0.4	094506-UM	TPS4	TIP15W
	2	3300X2F40	●	2	73	93	158	40	50	0.4	094506-UM	TPS4	TIP15W
	3	3300X3F40	●	2	106	126	191	40	50	0.4	094506-UM	TPS4	TIP15W
	4	3300X4F40	●	2	139	159	224	40	50	0.4	094506-UM	TPS4	TIP15W
	5	3300X5F40	●	2	172	192	257	40	50	0.4	094506-UM	TPS4	TIP15W
	6	3300X6F40	●	2	205	225	290	40	50	0.4	094506-UM	TPS4	TIP15W

INSERTS

Shape	Drill Diameter	Insert Number	Dimensions (mm)			Stock			Geometry
			D1	S1	Re	VP15TF	MC1020	MC5020	
 General purpose	ø17—ø19.5	SOMX063005-UM	6	3	0.5	●	●	●	
	ø20—ø22.5	073505-UM	7	3.5	0.5	●	●	●	
	ø23—ø27.5	084005-UM	8.3	4	0.5	●	●	●	
	ø28—ø33	094506-UM	9.7	4.5	0.6	●	●	●	

*MC1020 and MC5020 are made exclusively for use as an outer insert.