



POSITIVE

Insert Number		Dimensions (mm)			Hole Type
		D ₂	D ₃	B (°)	
RCGT RCMT	0602M0	2.8	3.8	R	B
	0803M0	3.4	4.5	R	B
	10T3M0	4.4	6.0	R	B
RGGM	2004M0	5.6	7.5	53°	C
SCMT SCMW	09T3	4.4	6.0	R	B
	1204	5.5	7.5	R	B
SPMW	0903	4.6	6.0	R	B
	1203	5.7	7.5	R	B
SPMT	0903	4.4	6.0	R	B
	1203	5.5	7.5	R	B
SPGX	0903	4.8	6.4	58°	D
	1203	5.9	7.7	58°	D
TCGT TCMT TCGW TCMW	0601	2.3	3.2	R	B
	0802	2.3	3.0	R	B
	0902	2.5	3.3	R	B
	1102	2.8	3.8	R	B
	1303	3.4	4.5	R	B
	16T3	4.4	6.0	R	B
TEGX	1603	4.4	6.1	88°	D
TPGX	0802	2.5	3.8	88°	C
	0902	3.0	4.3	88°	C
	1103	3.5	4.8	88°	C
	1603	4.8	6.5	58°	D
TPMX	0802	2.7	3.8	88°	C
	0902	3.2	4.3	88°	C
	1103	3.7	4.8	88°	C
	1603	4.8	6.4	58°	D
TPGB TPMB TPGH TPMH	0802	2.4	4.0	78°	D
	0902	2.9	4.3	78°	D
	1103	3.4	4.8	78°	D
	1603	4.4	6.5	78°	D
TPGT	1603	4.4	6.0	R	B
TPGV	0902	2.8	3.8	R	B
	1103	3.4	4.5	R	B

Insert Number		Dimensions (mm)			Hole Type
		D ₂	D ₃	B (°)	
VBET VBGT VBMT VBGW	1103	2.9	3.8	R	B
	1604	4.4	6.0	R	B
VCGT VCMT VCGW VCMW	0802	2.4	3.2	R	B
	1103	2.8	3.8	R	B
	1604	4.4	6.0	R	B
	2205	7.5	5.5	R	B
VDGX	1603	4.5	6.1	88°	D
VPET VPGT	0802	2.4	3.2	R	B
	1103	2.9	3.8	R	B
WBGT WBMT	0201	2.3	3.2	R	B
	L302	2.3	3.2	R	B
WCGT WCMT WCGW WCMW	0201	2.3	3.0	R	B
	L302	2.3	3.0	R	B
	0402	2.8	3.8	R	B
	06T3	4.4	6.0	R	B
WPGT WPMT	0402	2.8	3.8	R	B
	0603	4.4	6.0	R	B
XCMT	1503	2.8	3.8	R	B