





















INSERTS

Holder	Setting Geometry	Breaker	Geometry	Insert Geometry	Order Number	Hand	Coated	Dimensions (mm)			Max. Cut Off Diameter (mm)	
							VP15TF	W ₃	L ₃	Re		
Right Hand (R)		With Breaker			CTAT07080V5RR-B	R	★	0.7	4.5	0.05	8	
				10120V5RR-B	R	★	1.0	6.7	0.05	12		
				15120V5RR-B	R	★	1.5	6.7	0.05	12		
				20120V5RR-B	R	★	2.0	6.7	0.05	12		
					CTAT15120V5RR-BX	R	★	1.5	6.7	0.05	12	
				20120V5RR-BX	R	★	2.0	6.7	0.05	12		
					CTAT10120V5RN-B	N	★	1.0	6.7	0.05	12	
				15120V5RN-B	N	★	1.5	6.7	0.05	12		
				20120V5RN-B	N	★	2.0	6.7	0.05	12		
					CTAT15120V5RN-BX	N	★	1.5	6.7	0.05	12	
				20120V5RN-BX	N	★	2.0	6.7	0.05	12		
						CTAT10110V5RL-B	L	★	1.0	6.7	0.05	11
				15110V5RL-B	L	★	1.5	6.7	0.05	11		
				20110V5RL-B	L	★	2.0	6.7	0.05	11		
Left Hand (L)		Without Breaker				CTAT1012000RR	R	★	1.0	6.7	0	12
					1512000RR	R	★	1.5	6.7	0	12	
					2012000RR	R	★	2.0	6.7	0	12	
					CTAT07080V5LL-B	L	★	0.7	4.5	0.05	8	
					10120V5LL-B	L	★	1.0	6.7	0.05	12	
					15120V5LL-B	L	★	1.5	6.7	0.05	12	
					20120V5LL-B	L	★	2.0	6.7	0.05	12	
					CTAT10120V5LN-B	N	★	1.0	6.7	0.05	12	
					15120V5LN-B	N	★	1.5	6.7	0.05	12	
					20120V5LN-B	N	★	2.0	6.7	0.05	12	
					CTAT10110V5LR-B	R	★	1.0	6.7	0.05	11	
					15110V5LR-B	R	★	1.5	6.7	0.05	11	
				20110V5LR-B	R	★	2.0	6.7	0.05	11		
					CTAT1012000LL	L	★	1.0	6.7	0	12	
					1512000LL	L	★	1.5	6.7	0	12	
					2012000LL	L	★	2.0	6.7	0	12	

Right hand insert shown.

SMALL TOOLS