

GROOVING SYSTEM



GY SERIES (FACE GROOVING)

4

00° type holder

(Note 1) For modular blades and modular holders, please order separately.
 (Note 2) Please use right hand modular blade for right hand modular holder.

Insert	GY2M ^{GS}	Insert	GY2G ^{MF}
Insert	GY2M ^{GU}	Insert	GY2M ^{MS}
Insert	GY1G ^{GS}	Insert	GY2M ^{MM}



Right hand tool holder shown.


Seat Size	Insert Width W ₃ (mm)	Hand (R/L)	First Cut Diameter D ₁ (mm)		Max. Groove Depth ar (mm)	ID	Order Number			
			Min.	Max.			Modular Blade	Stock	Modular Holder	Stock
NEW E	2.39 2.50 2.74	★2 R	40	50	12	(4Q1R4E11)	GYM25RD-E12-040	●	GYHR3225P00-M25R	●
			50	60	12	(4Q1R4E12)	GYM25RD-E12-050	●		
			60	75	12	(4Q1R4E13)	GYM25RD-E12-060	●		
			75	100	12	(4Q1R4E14)	GYM25RD-E12-075	●		
			100	150	12	(4Q1R4E15)	GYM25RD-E12-100	●		
			135	200	12	(4Q1R4E16)	GYM25RD-E12-135	●		
			180	250	12	(4Q1R4E17)	GYM25RD-E12-180	●		
			40	50	12	(4J1R4E11)	GYM25RD-E12-040	●	GYHR3232P00-M25R	●
			50	60	12	(4J1R4E12)	GYM25RD-E12-050	●		
			60	75	12	(4J1R4E13)	GYM25RD-E12-060	●		
			75	100	12	(4J1R4E14)	GYM25RD-E12-075	●		
			100	150	12	(4J1R4E15)	GYM25RD-E12-100	●		
			135	200	12	(4J1R4E16)	GYM25RD-E12-135	●		
			180	250	12	(4J1R4E17)	GYM25RD-E12-180	●		

★1 Dimensions shown are when the gauge insert is used. If other insert geometries are used then L₁, L₂, F₁ and D₁ values may vary.

★2 Refer to page F062 for left hand tools.

Notes when selecting a modular blade (1)

- Select a modular blade for face grooving, so that the cutting diameter at the first pass is within the range of D₁ minimum and D₁ maximum that are described in the table of dimensions.



● : Inventory maintained.