





INTERNAL

Type	Thread Tolerance	Order Number	Coated		Pitch		Dimensions (mm)					Total Cutting Depth (mm)	Geometry
			VP10MF	VP15TF			D1	S1	Z1	Z2	Re		
					mm	thread/inch							
American UN	2B	MMT11IR320UN	★			32	6.35	3.04	0.6	0.6	0.04	0.46	Full form 
		11IR280UN	★			28	6.35	3.04	0.6	0.7	0.05	0.52	
		11IR240UN	●			24	6.35	3.04	0.7	0.8	0.09	0.61	
		11IR200UN	●			20	6.35	3.04	0.8	0.9	0.11	0.73	
		11IR180UN	●			18	6.35	3.04	0.8	1.0	0.12	0.81	
		11IR160UN	●			16	6.35	3.04	0.9	1.1	0.14	0.92	
		11IR140UN	●			14	6.35	3.04	0.9	1.1	0.11	1.05	
		16IR320UN	●			32	9.525	3.44	0.6	0.6	0.04	0.46	
		16IR280UN	●			28	9.525	3.44	0.6	0.7	0.05	0.52	
		16IR240UN	●			24	9.525	3.44	0.7	0.8	0.09	0.61	
		16IR200UN	●			20	9.525	3.44	0.8	0.9	0.11	0.73	
		16IR180UN	●			18	9.525	3.44	0.8	1.0	0.12	0.81	
		16IR160UN	●	●		16	9.525	3.44	0.9	1.1	0.14	0.92	
		16IR140UN	●	●		14	9.525	3.44	0.9	1.2	0.11	1.05	
		16IR130UN	●			13	9.525	3.44	1.0	1.3	0.10	1.13	
		16IR120UN	●	●		12	9.525	3.44	1.1	1.4	0.18	1.22	
		16IR110UN	●			11	9.525	3.44	1.1	1.5	0.13	1.33	
		16IR100UN	●			10	9.525	3.44	1.1	1.5	0.15	1.47	
		16IR090UN	●			9	9.525	3.44	1.2	1.7	0.17	1.63	
		16IR080UN	●			8	9.525	3.44	1.1	1.5	0.27	1.83	
		22IR070UN	●			7	12.7	4.64	1.6	2.3	0.23	2.09	
		22IR060UN	●			6	12.7	4.64	1.6	2.3	0.26	2.44	
		22IR050UN	●			5	12.7	4.64	1.6	2.3	0.32	2.93	
Whitworth for BSW, BSP	Medium Class A	MMT11IR190W	●			19	6.35	3.04	0.8	1.0	0.19	0.86	Full form 
		11IR140W	●			14	6.35	3.04	0.9	1.1	0.26	1.16	
		16IR280W	●			28	9.525	3.44	0.6	0.7	0.09	0.58	
		16IR260W	●			26	9.525	3.44	0.7	0.8	0.10	0.63	
		16IR200W	●			20	9.525	3.44	0.8	0.9	0.18	0.81	
		16IR190W	●	●		19	9.525	3.44	0.8	1.0	0.19	0.86	
		16IR180W	●			18	9.525	3.44	0.8	1.0	0.20	0.90	
		16IR160W	●			16	9.525	3.44	0.9	1.1	0.23	1.02	
		16IR140W	●	●		14	9.525	3.44	1.0	1.2	0.26	1.16	
		16IR120W	●			12	9.525	3.44	1.1	1.4	0.30	1.36	
		16IR110W	●	●		11	9.525	3.44	1.1	1.5	0.33	1.48	
		16IR100W	●			10	9.525	3.44	1.1	1.5	0.37	1.63	
		16IR090W	●			9	9.525	3.44	1.2	1.7	0.34	1.81	
		16IR080W	●			8	9.525	3.44	1.2	1.5	0.39	2.03	
		22IR070W	●			7	12.7	4.64	1.6	2.3	0.46	2.32	
		22IR060W	●			6	12.7	4.64	1.6	2.3	0.53	2.71	
		22IR050W	●			5	12.7	4.64	1.7	2.4	0.66	3.25	
BSPT	Standard BSPT	MMT11IR190BSPT	●			19	6.35	3.04	0.8	0.9	0.14	0.86	Full form 
		11IR140BSPT	●			14	6.35	3.04	0.9	1.0	0.26	1.16	
		16IR190BSPT	★	★		19	9.525	3.44	0.8	0.9	0.14	0.86	
		16IR140BSPT	★	★		14	9.525	3.44	1.0	1.2	0.26	1.16	
		16IR110BSPT	★	★		11	9.525	3.44	1.1	1.5	0.33	1.48	
Round DIN 405	7H	MMT16IR100RD	●			10	9.525	3.44	1.1	1.2	0.55	1.27	Full form 
		16IR080RD	●			8	9.525	3.44	1.4	1.4	0.70	1.59	
		16IR060RD	●			6	9.525	3.44	1.4	1.5	0.93	2.12	
		22IR040RD	●			4	12.7	4.64	2.2	2.3	1.40	3.18	