



SMT INSERTS (Threading)

Order Number	Stock	Thread Pitch (mm)	Dimensions (mm)	Geometry
	Carbide		Re	
	UTi20T			
SMTTR16036001	★	1.0—1.5	0.1	
16036002	★	1.75—2.0	0.2	

(Note) Wet cutting is recommended.

SMG INSERTS (Grooving)

Order Number	Stock				Groove Width W3	Dimensions (mm)				Geometry
	Cermet		Carbide			L3	D1	S1	C	
	NX2525		UTi20T	HTi10						
SMGTR16X2050				★	0.5	1.5	9.525	2.0	—	
16X2060	□		□	□	0.6	1.5	9.525	2.0	—	
16X2050C	★		★	★	0.5	1.5	9.525	2.0	0.05	
16X2060C	□		□	□	0.6	1.5	9.525	2.0	0.05	
16X2070C	□		□	□	0.7	2.0	9.525	2.0	0.05	
16X2075C	★		★	★	0.75	2.0	9.525	2.0	0.05	
16X2080C	★		★	★	0.8	2.0	9.525	2.0	0.1	
16X2090C	□		□	□	0.9	2.0	9.525	2.0	0.1	
16X2095C	★		★	★	0.95	2.0	9.525	2.0	0.1	
16X2100C	★		★	★	1.0	2.5	9.525	2.0	0.1	
16X2110C	□		□	□	1.1	2.5	9.525	2.0	0.1	
16X2120C	★		★	★	1.2	2.5	9.525	2.0	0.1	
16X2130C	□		□	□	1.3	2.5	9.525	2.0	0.1	