

Unit : mm

Order Number	R	D1	ap	L3	D5	B2	L1	D4	Flutes	Stock	Type	Effective length for inclined angle			
												30°	1°	2°	3°
MP2XLBR0020N040	0.2	0.4	0.3	4	0.37	8.4°	50	4	2	★	1	4.2	4.3	4.7	5.2
R0020N045	0.2	0.4	0.3	4.5	0.37	8°	50	4	2	★	1	4.7	4.9	5.3	5.9
R0020N050	0.2	0.4	0.3	5	0.37	7.7°	50	4	2	★	1	5.2	5.4	5.9	6.6
R0020N055	0.2	0.4	0.3	5.5	0.37	7.5°	50	4	2	★	1	5.7	6	6.5	7.2
R0020N060	0.2	0.4	0.3	6	0.37	7.2°	50	4	2	★	1	6.2	6.5	7.1	7.9
R0025N010	0.25	0.5	0.37	1	0.47	11°	50	4	2	★	1	1	1	1.1	1.2
R0025N015	0.25	0.5	0.37	1.5	0.47	10.4°	50	4	2	★	1	1.5	1.6	1.7	1.9
R0025N015S06	0.25	0.5	0.37	1.5	0.47	11°	50	6	2	★	1	1.5	1.6	1.7	1.9
R0025N020	0.25	0.5	0.37	2	0.47	9.9°	50	4	2	★	1	2.1	2.1	2.3	2.6
R0025N020S06	0.25	0.5	0.37	2	0.47	10.6°	50	6	2	★	1	2.1	2.1	2.3	2.6
R0025N025	0.25	0.5	0.37	2.5	0.47	9.5°	50	4	2	★	1	2.6	2.7	2.9	3.2
R0025N025S06	0.25	0.5	0.37	2.5	0.47	10.3°	50	6	2	★	1	2.6	2.7	2.9	3.2
R0025N030	0.25	0.5	0.37	3	0.47	9.1°	50	4	2	★	1	3.1	3.2	3.5	3.9
R0025N030S06	0.25	0.5	0.37	3	0.47	10°	50	6	2	★	1	3.1	3.2	3.5	3.9
R0025N035	0.25	0.5	0.37	3.5	0.47	8.7°	50	4	2	★	1	3.6	3.8	4.1	4.6
R0025N040	0.25	0.5	0.37	4	0.47	8.3°	50	4	2	★	1	4.1	4.3	4.7	5.2
R0025N045	0.25	0.5	0.37	4.5	0.47	8°	50	4	2	★	1	4.7	4.9	5.3	5.9
R0025N050	0.25	0.5	0.37	5	0.47	7.7°	50	4	2	★	1	5.2	5.4	5.9	6.6
R0025N055	0.25	0.5	0.37	5.5	0.47	7.4°	50	4	2	★	1	5.7	6	6.5	7.2
R0025N060	0.25	0.5	0.37	6	0.47	7.2°	50	4	2	★	1	6.2	6.5	7.1	7.9
R0025N070	0.25	0.5	0.37	7	0.47	6.7°	50	4	2	★	1	7.3	7.6	8.3	9.2
R0025N080	0.25	0.5	0.37	8	0.47	6.3°	50	4	2	★	1	8.3	8.7	9.5	10.5
R0025N090	0.25	0.5	0.37	9	0.47	5.9°	50	4	2	★	1	9.4	9.8	10.7	11.9
R0025N100	0.25	0.5	0.37	10	0.47	5.6°	50	4	2	★	1	10.4	10.9	11.9	13.2
R0030N015	0.3	0.6	0.45	1.5	0.57	10.4°	50	4	2	★	1	1.5	1.6	1.8	2
R0030N015S06	0.3	0.6	0.45	1.5	0.57	11°	50	6	2	★	1	1.5	1.6	1.8	2
R0030N020	0.3	0.6	0.45	2	0.57	9.9°	50	4	2	★	1	2.1	2.2	2.4	2.6
R0030N020S06	0.3	0.6	0.45	2	0.57	10.6°	50	6	2	★	1	2.1	2.2	2.4	2.6
R0030N025	0.3	0.6	0.45	2.5	0.57	9.4°	50	4	2	★	1	2.6	2.7	3	3.3
R0030N030	0.3	0.6	0.45	3	0.57	9°	50	4	2	★	1	3.1	3.3	3.6	4
R0030N030S06	0.3	0.6	0.45	3	0.57	9.9°	50	6	2	★	1	3.1	3.3	3.6	4
R0030N035	0.3	0.6	0.45	3.5	0.57	8.6°	50	4	2	★	1	3.7	3.8	4.2	4.6
R0030N040	0.3	0.6	0.45	4	0.57	8.2°	50	4	2	★	1	4.2	4.4	4.8	5.3
R0030N040S06	0.3	0.6	0.45	4	0.57	9.3°	50	6	2	★	1	4.2	4.4	4.8	5.3
R0030N045	0.3	0.6	0.45	4.5	0.57	7.9°	50	4	2	★	1	4.7	4.9	5.4	5.9
R0030N050	0.3	0.6	0.45	5	0.57	7.6°	50	4	2	★	1	5.2	5.5	6	6.6
R0030N050S06	0.3	0.6	0.45	5	0.57	8.8°	50	6	2	★	1	5.2	5.5	6	6.6
R0030N055	0.3	0.6	0.45	5.5	0.57	7.3°	50	4	2	★	1	5.8	6	6.6	7.3
R0030N060	0.3	0.6	0.45	6	0.57	7.1°	50	4	2	★	1	6.3	6.6	7.2	7.9
R0030N060S06	0.3	0.6	0.45	6	0.57	8.3°	50	6	2	★	1	6.3	6.6	7.2	7.9
R0030N065	0.3	0.6	0.45	6.5	0.57	6.8°	50	4	2	★	1	6.8	7.1	7.8	8.6
R0030N070	0.3	0.6	0.45	7	0.57	6.6°	50	4	2	★	1	7.3	7.6	8.4	9.3
R0030N080	0.3	0.6	0.45	8	0.57	6.2°	50	4	2	★	1	8.4	8.7	9.6	10.6
R0030N080S06	0.3	0.6	0.45	8	0.57	7.6°	50	6	2	★	1	8.4	8.7	9.6	10.6
R0030N085	0.3	0.6	0.45	8.5	0.57	6°	50	4	2	★	1	8.9	9.3	10.2	11.3
R0030N090	0.3	0.6	0.45	9	0.57	5.8°	50	4	2	★	1	9.4	9.8	10.8	11.9
R0030N095	0.3	0.6	0.45	9.5	0.57	5.7°	50	4	2	★	1	9.9	10.4	11.4	12.6
R0030N100	0.3	0.6	0.45	10	0.57	5.5°	50	4	2	★	1	10.5	10.9	12	13.2
R0030N110	0.3	0.6	0.45	11	0.57	5.2°	50	4	2	★	1	11.5	12	13.2	14.6
R0030N120	0.3	0.6	0.45	12	0.57	5°	50	4	2	★	1	12.5	13.1	14.4	15.9
R0040N020	0.4	0.8	0.6	2	0.77	9.9°	50	4	2	★	1	2.1	2.2	2.4	2.6
R0040N020S06	0.4	0.8	0.6	2	0.77	10.6°	50	6	2	★	1	2.1	2.2	2.4	2.6

SQUARE

BALL

RADIUS

TAPER

SOLID END MILLS