

Unit : mm

Order Number	R	D1	ap	L3	D5	L1	D4	Flutes	Stock	Type
VF2SBR0800S16	8	16	30	—	—	140	16	2	●	4
R1000S20	10	20	38	—	—	160	20	2	●	4

SQUARE

BALL

RADIUS

TAPER

SOLID END MILLS

VF2SSB

Ball nose, Short cut length, 2 flute, For hardened materials

VF2SB


Ball nose, Short cut length, 2 flute, For hardened materials

RECOMMENDED CUTTING CONDITIONS

Work material	Hardened steel (45—55HRC)					Hardened steel (55—62HRC)					Hardened steel (62—70HRC)				
	X40CrMoV51					X210Cr12					070M55, 1.3343 (W6Mo5Cr4V2)				
	$\alpha \leq 15^\circ$		$\alpha > 15^\circ$		Depth of cut (mm)	$\alpha \leq 15^\circ$		$\alpha > 15^\circ$		Depth of cut (mm)	$\alpha \leq 15^\circ$		$\alpha > 15^\circ$		Depth of cut (mm)
R (mm)	Revolution (min ⁻¹)	Feed rate (mm/min)	Revolution (min ⁻¹)	Feed rate (mm/min)		Revolution (min ⁻¹)	Feed rate (mm/min)	Revolution (min ⁻¹)	Feed rate (mm/min)		Revolution (min ⁻¹)	Feed rate (mm/min)	Revolution (min ⁻¹)	Feed rate (mm/min)	
R 0.1	40000	320	40000	240	0.003	40000	320	40000	160	0.003	40000	320	40000	160	0.002
R 0.15	40000	640	40000	560	0.01	40000	640	40000	400	0.007	40000	640	40000	400	0.005
R 0.2	40000	1600	40000	1200	0.02	40000	1400	40000	1000	0.015	40000	1200	40000	1000	0.01
R 0.3	40000	3200	40000	1600	0.03	40000	2800	40000	1200	0.025	40000	2000	40000	1200	0.02
R 0.4	40000	6400	40000	2400	0.05	40000	4000	40000	1600	0.04	40000	2800	40000	1600	0.03
R 0.5	40000	8000	40000	3200	0.06	40000	5600	40000	2400	0.05	40000	3600	32000	1300	0.04
R 0.75	40000	9600	40000	4000	0.09	40000	7200	32000	2500	0.075	32000	4500	21000	1200	0.05
R 1	40000	9600	39000	4700	0.11	40000	8000	24000	2400	0.1	24000	3800	16000	1000	0.07
R 1.25	40000	10400	32000	4500	0.12	37000	8100	19000	2300	0.11	19000	3400	13000	1000	0.08
R 1.5	40000	12000	27000	4300	0.13	32000	7700	16000	2200	0.12	16000	3200	11000	880	0.09
R 2	32000	10880	20000	3600	0.15	24000	6200	12000	1900	0.13	12000	2400	8000	800	0.1
R 2.5	25000	9000	16000	2900	0.2	19000	5300	9600	1700	0.15	9600	2100	6000	600	0.1
R 3	21000	8400	13000	2600	0.25	16000	4800	8000	1600	0.2	8000	1700	5000	600	0.11
R 4	16000	6400	10000	2000	0.3	12000	3600	6000	1200	0.2	6000	1400	4000	480	0.11
R 5	13000	5200	8000	1700	0.5	10000	3200	4800	960	0.2	4800	1100	3000	420	0.12
R 6	9000	3600	6000	1300	0.5	7000	2200	3600	720	0.3	3600	860	2200	310	0.12
R 8	6000	2400	4000	1000	0.5	5000	1600	2500	500	0.3	2500	650	1500	240	0.15
R10	4500	1800	3000	780	0.5	4000	1300	1800	360	0.3	1800	470	1000	160	0.15

Depth of cut

Please select a pick feed based on the required surface finishes in reference to "Pitch Selection of Pick Feed" on page N021.



≤ Please refer to the list above for depth of cut.

R:Radius

- 1) α is the inclination angle of the machined surface.
- 2) If the depth of cut is shallow, the revolution and feed rate can be increased.
- 3) If the rigidity of the machine or the work materials installation is very low, or chattering and noise are generated, reduce the revolution and feed rate proportionately.

