

Unit : mm

Order Number	D1	R	ap	L3	D5	B2	L1	D4	Flutes	Stock	Type	Effective length for inclined angle			
												30°	1°	2°	3°
VCPSRBD0150N06R05	1.5	0.5	1.5	6	1.44	9°	50	6	2	●	1	6.3	6.6	7.1	7.7
D0150N10R01	1.5	0.1	1.5	10	1.44	6.9°	50	6	2	●	1	10.6	11	11.8	12.7
D0150N10R02	1.5	0.2	1.5	10	1.44	7°	50	6	2	●	1	10.5	11	11.8	12.7
D0150N10R03	1.5	0.3	1.5	10	1.44	7°	50	6	2	●	1	10.5	10.9	11.8	12.7
D0150N10R05	1.5	0.5	1.5	10	1.44	7.1°	50	6	2	●	1	10.5	10.9	11.7	12.6
D0150N15R01	1.5	0.1	1.5	15	1.44	5.5°	50	6	2	●	1	15.8	16.3	17.5	18.9
D0150N15R02	1.5	0.2	1.5	15	1.44	5.5°	50	6	2	●	1	15.8	16.3	17.5	18.9
D0150N15R03	1.5	0.3	1.5	15	1.44	5.5°	50	6	2	●	1	15.7	16.3	17.5	18.9
D0150N15R05	1.5	0.5	1.5	15	1.44	5.7°	50	6	2	●	1	15.7	16.3	17.4	18.6
D0150N20R03	1.5	0.3	1.5	20	1.44	4.7°	60	6	2	●	1	20.9	21.6	22.9	24.5
D0150N20R05	1.5	0.5	1.5	20	1.44	4.8°	60	6	2	●	1	20.9	21.5	22.8	24.2
D0200N06R01	2	0.1	2	6	1.9	9.4°	50	6	4	●	1	6.3	6.6	6.9	7.5
D0200N06R02	2	0.2	2	6	1.9	9.7°	50	6	4	●	1	6.3	6.6	6.8	7.4
D0200N06R03	2	0.3	2	6	1.9	10°	50	6	4	●	1	6.3	6.6	6.7	7.4
D0200N06R05	2	0.5	2	6	1.9	10.3°	50	6	4	●	1	6.3	6.5	6.5	7.4
D0200N10R01	2	0.1	2	10	1.9	7.6°	50	6	4	●	1	10.5	10.9	11.4	12
D0200N10R02	2	0.2	2	10	1.9	7.7°	50	6	4	●	1	10.5	10.8	11.2	12
D0200N10R03	2	0.3	2	10	1.9	7.8°	50	6	4	●	1	10.5	10.8	11.1	11.9
D0200N10R05	2	0.5	2	10	1.9	8°	50	6	4	●	1	10.5	10.8	10.9	11.9
D0200N15R01	2	0.1	2	15	1.9	5.9°	50	6	4	●	1	15.7	16.1	16.8	17.5
D0200N15R02	2	0.2	2	15	1.9	5.9°	50	6	4	●	1	15.7	16.1	16.7	17.5
D0200N15R03	2	0.3	2	15	1.9	6°	50	6	4	●	1	15.7	16.1	16.6	17.4
D0200N15R05	2	0.5	2	15	1.9	6.1°	50	6	4	●	1	15.6	16.1	16.3	17.4
D0200N20R03	2	0.3	2	20	1.9	4.8°	60	6	4	●	1	20.8	21.4	21.9	22.9
D0200N20R05	2	0.5	2	20	1.9	4.9°	60	6	4	●	1	20.8	21.4	21.7	22.9
D0200N25R03	2	0.3	2	25	1.9	4°	60	6	4	●	1	26	26.6	27.5	28.3
D0200N25R05	2	0.5	2	25	1.9	4°	60	6	4	●	1	26	26.6	27	28.2
D0250N08R01	2.5	0.1	2.5	8	2.4	8.6°	50	6	4	●	1	8.4	8.7	9.2	9.9
D0250N08R02	2.5	0.2	2.5	8	2.4	8.7°	50	6	4	●	1	8.4	8.7	9	9.9
D0250N08R03	2.5	0.3	2.5	8	2.4	8.8°	50	6	4	●	1	8.4	8.7	8.9	9.9
D0250N08R05	2.5	0.5	2.5	8	2.4	9°	50	6	4	●	1	8.4	8.7	8.7	9.9
D0250N08R10	2.5	1	2.5	8	2.4	9.4°	50	6	4	●	1	8.3	8.7	8.2	9.9
D0250N15R03	2.5	0.3	2.5	15	2.4	5.5°	50	6	4	●	1	15.7	16.1	16.6	17.5
D0250N15R05	2.5	0.5	2.5	15	2.4	5.6°	50	6	4	●	1	15.6	16.1	16.3	17.5
D0250N15R10	2.5	1	2.5	15	2.4	5.7°	50	6	4	●	1	15.6	16.1	15.8	17.5
D0300N10R01	3	0.1	3	10	2.9	6.6°	60	6	4	●	1	10.5	10.9	11.4	12.3
D0300N10R02	3	0.2	3	10	2.9	6.6°	60	6	4	●	1	10.5	10.8	11.2	12.3
D0300N10R03	3	0.3	3	10	2.9	6.6°	60	6	4	●	1	10.5	10.8	11.1	12.3
D0300N10R05	3	0.5	3	10	2.9	6.7°	60	6	4	●	1	10.5	10.8	10.9	12.4
D0300N10R10	3	1	3	10	2.9	7°	60	6	4	●	1	10.4	10.8	10.4	12.4
D0300N15R01	3	0.1	3	15	2.9	4.8°	60	6	4	●	1	15.7	16.1	16.8	17.7
D0300N15R02	3	0.2	3	15	2.9	4.8°	60	6	4	●	1	15.7	16.1	16.7	17.8
D0300N15R03	3	0.3	3	15	2.9	4.8°	60	6	4	●	1	15.7	16.1	16.6	17.8
D0300N15R05	3	0.5	3	15	2.9	4.8°	60	6	4	●	1	15.6	16.1	16.3	17.8
D0300N15R10	3	1	3	15	2.9	5°	60	6	4	●	1	15.6	16.1	15.8	17.8
D0300N20R01	3	0.1	3	20	2.9	3.7°	60	6	4	●	1	20.8	21.4	22.1	23.1
D0300N20R02	3	0.2	3	20	2.9	3.7°	60	6	4	●	1	20.8	21.4	22	23.1
D0300N20R03	3	0.3	3	20	2.9	3.8°	60	6	4	●	1	20.8	21.4	21.9	23.2
D0300N20R05	3	0.5	3	20	2.9	3.8°	60	6	4	●	1	20.8	21.4	21.7	23.2
D0300N20R10	3	1	3	20	2.9	3.9°	60	6	4	●	1	20.8	21.3	21.2	23.2
D0300N30R03	3	0.3	3	30	2.9	2.6°	70	6	4	●	1	31.1	31.8	32.5	★
D0300N30R05	3	0.5	3	30	2.9	2.6°	70	6	4	●	1	31.1	31.8	32.2	★

★ No interference

SQUARE

BALL

RADIUS

TAPER

SOLID END MILLS