

CRN COATED END MILLS

CRN2XLB

Ball nose, Long neck, 2 flute, For copper electrodes

Unit : mm

CARBIDE

SQUARE

BALL

RADIUS

TAPER

SOLID END MILLS

Order Number	R	D1	ap	L3	D5	B2	L1	D4	Flutes	Stock	Type	Effective length for inclined angle			
												30'	1°	2°	3°
CRN2XLBR0075N160S04	0.75	1.5	1.5	16	1.44	3.6°	55	4	2	●	1	16.8	17.3	18.6	20
R0075N160S06	0.75	1.5	1.5	16	1.44	5.4°	55	6	2	●	1	16.8	17.3	18.6	20
R0075N180S04	0.75	1.5	1.5	18	1.44	3.3°	55	4	2	●	1	18.8	19.5	20.9	22.5
R0075N180S06	0.75	1.5	1.5	18	1.44	5°	60	6	2	●	1	18.8	19.5	20.9	22.5
R0075N200S04	0.75	1.5	1.5	20	1.44	3°	55	4	2	●	1	20.9	21.6	23.2	*
R0075N200S06	0.75	1.5	1.5	20	1.44	4.6°	60	6	2	●	1	20.9	21.6	23.2	25
R0100N080S04	1	2	2	8	1.90	5.3°	50	4	2	●	1	8.3	8.7	9.2	9.9
R0100N080S06	1	2	2	8	1.90	7.8°	50	6	2	●	1	8.3	8.7	9.2	9.9
R0100N100S04	1	2	2	10	1.90	4.5°	50	4	2	●	1	10.4	10.8	11.5	12.4
R0100N100S06	1	2	2	10	1.90	6.9°	50	6	2	●	1	10.4	10.8	11.5	12.4
R0100N120S04	1	2	2	12	1.90	3.9°	50	4	2	●	1	12.5	12.9	13.8	14.9
R0100N120S06	1	2	2	12	1.90	6.1°	50	6	2	●	1	12.5	12.9	13.8	14.9
R0100N140S04	1	2	2	14	1.90	3.4°	50	4	2	●	1	14.6	15.1	16.1	17.4
R0100N140S06	1	2	2	14	1.90	5.6°	55	6	2	●	1	14.6	15.1	16.1	17.4
R0100N160S04	1	2	2	16	1.90	3.1°	55	4	2	●	1	16.7	17.2	18.4	19.9
R0100N160S06	1	2	2	16	1.90	5.1°	55	6	2	●	1	16.7	17.2	18.4	19.9
R0100N200S04	1	2	2	20	1.90	2.5°	60	4	2	●	1	20.8	21.5	23	*
R0100N200S06	1	2	2	20	1.90	4.3°	60	6	2	●	1	20.8	21.5	23	24.8
R0100N250S06	1	2	2	25	1.90	3.7°	65	6	2	●	1	26	26.8	28.8	31
R0100N300S06	1	2	2	30	1.90	3.2°	70	6	2	●	1	31.1	32.2	34.5	37.3
R0150N160S06	1.5	3	3	16	2.90	4.3°	60	6	2	●	1	16.6	17.2	18.4	19.7
R0150N250S06	1.5	3	3	25	2.90	3°	70	6	2	●	1	26	26.8	28.7	*
R0150N350S06	1.5	3	3	35	2.90	2.2°	80	6	2	●	1	36.3	37.5	40.2	*
R0200N160S06	2	4	4	16	3.90	3.2°	70	6	2	●	1	16.6	17.1	18.3	19.6
R0200N200S06	2	4	4	20	3.90	2.7°	70	6	2	●	1	20.8	21.4	22.9	*
R0200N300S06	2	4	4	30	3.90	1.8°	70	6	2	●	1	31.1	32.1	*	*
R0200N400S06	2	4	4	40	3.90	1.4°	90	6	2	●	1	41.4	42.8	*	*
R0200N500S06	2	4	4	50	3.90	1.2°	100	6	2	●	1	51.8	53.5	*	*
R0250N200S06	2.5	5	5	20	4.90	1.5°	70	6	2	●	1	20.7	21.4	*	*
R0250N300S06	2.5	5	5	30	4.90	1°	80	6	2	●	1	31.1	*	*	*
R0300N300S06	3	6	6	30	5.85	—	80	6	2	●	1	*	*	*	*
R0300N500S06	3	6	6	50	5.85	—	100	6	2	●	1	*	*	*	*

* No interference

● : Inventory maintained.