


ALIMASTER END MILLS

AM3SSRB

Corner radius end mill, Short cut length, 3 flute, Relieved neck



Carbon Steel, Alloy Steel, Cast Iron (≤30HRC)	Tool Steel, Pre-Hardened Steel, Hardened Steel (≤45HRC)	Hardened Steel (≤55HRC)	Hardened Steel (>55HRC)	Austenitic Stainless Steel	Titanium Alloy, Heat Resistant Alloy	Copper Alloy	Aluminium Alloy
						○	◎



Type1



D1 ≤ 12	D1 > 12			
0 - 0.020	0 - 0.030			

- High efficiency machining of aluminium alloy.

Unit : mm

Order Number	D1	R	ap	L3	D5	L1	D4	Flutes	Stock	Type
AM3SSRBD1200A075R100	12	1	15	30	11.4	75	12	3	●	1
D1200A075R160	12	1.6	15	30	11.4	75	12	3	●	1
D1200A075R250	12	2.5	15	30	11.4	75	12	3	●	1
D1200A075R320	12	3.2	15	30	11.4	75	12	3	●	1
D1200A075R400	12	4	15	30	11.4	75	12	3	●	1
D1200A100R100	12	1	15	35	11.4	100	12	3	●	1
D1200A100R160	12	1.6	15	35	11.4	100	12	3	●	1
D1200A100R250	12	2.5	15	35	11.4	100	12	3	●	1
D1200A100R320	12	3.2	15	35	11.4	100	12	3	●	1
D1200A100R400	12	4	15	35	11.4	100	12	3	●	1
D1200A125R100	12	1	15	40	11.4	125	12	3	●	1
D1200A125R160	12	1.6	15	40	11.4	125	12	3	●	1
D1200A125R250	12	2.5	15	40	11.4	125	12	3	●	1
D1200A125R320	12	3.2	15	40	11.4	125	12	3	●	1
D1200A125R400	12	4	15	40	11.4	125	12	3	●	1
D1600A075R100	16	1	15	30	15.4	75	16	3	●	1
D1600A075R160	16	1.6	15	30	15.4	75	16	3	●	1
D1600A075R250	16	2.5	15	30	15.4	75	16	3	●	1
D1600A075R320	16	3.2	15	30	15.4	75	16	3	●	1
D1600A075R400	16	4	15	30	15.4	75	16	3	●	1
D1600A100R100	16	1	15	40	15.4	100	16	3	●	1
D1600A100R160	16	1.6	15	40	15.4	100	16	3	●	1
D1600A100R250	16	2.5	15	40	15.4	100	16	3	●	1
D1600A100R320	16	3.2	15	40	15.4	100	16	3	●	1
D1600A100R400	16	4	15	40	15.4	100	16	3	●	1
D1600A125R100	16	1	15	45	15.4	125	16	3	●	1
D1600A125R160	16	1.6	15	45	15.4	125	16	3	●	1
D1600A125R250	16	2.5	15	45	15.4	125	16	3	●	1
D1600A125R320	16	3.2	15	45	15.4	125	16	3	●	1
D1600A125R400	16	4	15	45	15.4	125	16	3	●	1
D2000A100R100	20	1	20	40	18.0	100	20	3	●	1
D2000A100R160	20	1.6	20	40	18.0	100	20	3	●	1
D2000A100R250	20	2.5	20	40	18.0	100	20	3	●	1
D2000A100R320	20	3.2	20	40	18.0	100	20	3	●	1

● : Inventory maintained.