

VAMFPR

Roughing type, Medium cut length, 4–6 flute, Fine pitch form






D1 ≤ 20

22 ≤ D1 ≤ 28

D1 ≥ 30

Carbon Steel, Alloy Steel, Cast Iron (≤30HRC)	Tool Steel, Pre-Hardened Steel, Hardened Steel (≤45HRC)	Hardened Steel (≤55HRC)	Hardened Steel (>55HRC)	Austenitic Stainless Steel	Titanium Alloy, Heat Resistant Alloy	Copper Alloy	Aluminium Alloy
◎	○			◎	○		



- Roughing 4–6 flute end mill with high grade HSS substrate and Violet coating for general use.

Unit : mm

Order Number	D1	ap	L1	D4	Flutes	Stock	Type
VAMFPRD0500	5	15	80	6	4	●	1
D0600	6	17	80	6	4	●	2
D0700	7	22	80	8	4	●	1
D0800	8	28	85	8	4	●	2
D0900	9	28	95	10	4	●	1
D1000	10	34	100	10	4	●	2
D1200	12	40	110	12	4	●	2
D1400	14	40	110	12	4	●	3
D1500	15	40	120	16	4	●	1
D1600	16	48	125	16	4	●	2
D1800	18	48	125	16	4	●	3
D2000	20	57	145	20	4	●	2
D2200	22	57	145	20	5	●	3
D2400	24	68	150	25	5	●	1
D2500	25	68	150	25	5	●	2
D2800	28	68	160	25	5	●	3
D3000	30	68	165	25	6	●	3
D3200	32	80	175	32	6	●	2
D3500	35	80	175	32	6	★	3
D4000	40	94	185	32	6	★	3
D4500	45	94	200	42	6	★	3
D5000	50	113	200	42	6	★	3

● : Inventory maintained. ★ : Inventory maintained in Japan.

SQUARE

BALL

RADIUS

TAPER

SOLID END MILLS

HSS